

BLOCKOUT

10mm DUETTE® NIGHTFALL FABRIC

Applications

DUETTE® Shades

Control Systems

Standard Cordlock

- Standard Bottom-up
- Top Down
- Top Down - Bottom-up
- Duo-lite

ULTRAGLIDE® Shades

- Standard Bottom-up
- Top Down
- Top Down - Bottom-up
- Duo-lite

PowerRise

EasyRise

Special Shapes

Motorisation

Composition

100% Spunbond Polyester
non woven, laminated to a
metallised polyester film

Vane Size

10mm

Colour Fastness

6-7 Blue Scale

10 Colours Available

Product: DUETTE® Shades in Nightfall Fabric Colour: Seal Taupe



HunterDouglasCommercial

WINDOW COVERINGS

10mm DUETTE® Nightfall Blockout Fabric

features and benefits

Fabric Specifications

10mm pleats. 100% Spunbond polyester non woven, laminated to a metallised polyester film. Blockout, coloured face with white backing.

Energy Efficiency

DUETTE® Shades provide superior insulation and energy efficiency to regulate temperature and minimise heating and cooling loads.

Design Flexibility

DUETTE® Shades are available in a range of different sizes to suit commercial applications and can be manufactured to fit special window shapes.

Blockout

All colours in the range block light providing a high level of privacy.

10 Colours

A range of neutrals & great new season designer colours.

UV Resistant

99% UV blockage.

Solar Optical Properties and COMFORT RATING Guide#

COLOUR	Ts	Rs	As	Tl	Rl	Al	Tuv	Sc	Heat Protection	Insulation	Shade Factor	Glare Reduction	UV Protection
Daisy White*	0	55	45	0	39	61	0	0.37	◆◆◆◆	◆◆◆◆◆◆	◆◆◆◆◆◆◆◆	◆◆◆◆◆◆◆◆	◆◆◆◆◆◆◆◆

*US test results

Solar Optical Properties Guide

- Ts - Heat Transmittance (%)
- Rs - Heat Reflectance (%)
- As - Heat Absorbance (%)
- Tl - Light Transmittance (%)
- Rl - Light Reflectance (%)
- Al - Light Absorbance (%)
- Tuv - Ultraviolet Transmittance (%)
- Sc - Shading Coefficient

COMFORT RATING Guide#

- ◆◆◆◆ Highest level of protection/performance
- ◆◆◆ High level of protection/performance
- ◆◆ Medium level of protection/performance
- ◆ Low level of protection/performance
- ◆ No protection

COMFORT RATING Guide has been devised by Hunter Douglas Limited with the assistance of Canesis Pty Ltd - an Independent Australian Fibre and Textile Research and Development Company.



Heat Protection



Insulation



Glare Reduction



UV Protection



Shade Factor

Fire Retardant

Complies with the General Requirements of the Building Code of Australia for Fire Hazard Properties of materials in buildings.

Ignitability Index [Range 0-20]	0	Heat Evolved Index [Range 0-10]	0
Spread of Flame Index [Range 0-10]	0	Smoke Developed Index [Range 0-10]	0-1

HunterDouglasCommercial

WINDOW COVERINGS

To see how Hunter Douglas Commercial Window Coverings can transform your next project call **1300 733 078**.

www.hunterdouglascommercial.com.au

© Copyright 2008. © Registered Trade Marks of Hunter Douglas Limited (ABN 98 009 675 709).
10.08_C7759/10mm DUETTE® Nightfall