

# TRANSLUCENT

## SERENE FABRIC

### Applications

Roller Blinds

Panel Glide

Vertical Blinds – 89mm Blades  
– 127mm Blades

### Composition

100% Polyester

### Weight

180gsm ± 20gsm

### Fabric Thickness

0.35mm ± 0.05mm

### Roll Width

2.4m

### Colour Fastness

6-7 Blue Scale

### Stiffness

70mm

### 12 Colours Available

### Low VOCs

### MULTIVISION® Concept

Product: Serene Translucent Fabric Colour: White



**HunterDouglasCommercial**

WINDOW COVERINGS

# Serene Translucent Fabric

## features and benefits

### 100% Polyester

### 12 Colours

A range of neutrals & great new season designer colours.

### Textured Basecloth

Gives fabric a great look & feel as well as a durable easy clean surface.

### UV Resistant

All colours meet Australian Standards for colour fastness to resist fading.

### Oeko-Tex "Confidence in Textiles"

Synonymous worldwide with responsible textile manufacture - from the raw materials to the finished product. The Oeko-Tex Standard 100 is a test and certification system for textile raw materials, intermediate and end products at all processing stages that is consistent worldwide. Serene Translucent Fabric has been tested for harmful substances according to Oeko-Tex Standard 100.

### VOCs

Serene Translucent Fabric has been tested and does not exceed the maximum VOC (Volatile Organic Compound) criteria specified by the Green Council of Australia (IEQ-11).

### MULTIVISION® Concept

MULTIVISION® is a group of fabrics that are perceived to be the same colour tone, but have different opacities. A number of Serene Translucent Fabric colours have been selected for the MULTIVISION® Concept. For more information refer to the Hunter Douglas Commercial MULTIVISION® Brochure.

## Solar Optical Properties and COMFORT RATING Guide\*

COLOUR	Ts	Rs	As	Tl	Rl	Al	Tuv	Sc	Heat Protection	Insulation	Shade Factor	Glare Reduction	UV Protection
White	29	61	10	21	56	23	<0.5	0.40	◆◆◆◆◆	◆◆	◆◆	◆◆	◆
Grey	6	40	54	4	40	56	0	0.49	◆◆◆◆◆	◆◆	◆◆◆◆◆	◆◆◆◆◆	◆◆◆◆◆
Black	1	5	94	0	5	95	0	0.72	◆◆◆	◆◆	◆◆◆◆◆	Blockout	◆◆◆◆◆

### Solar Optical Properties Guide

- Ts - Heat Transmittance (%)
- Rs - Heat Reflectance (%)
- As - Heat Absorbance (%)
- Tl - Light Transmittance (%)
- Rl - Light Reflectance (%)
- Al - Light Absorbance (%)
- Tuv - Ultraviolet Transmittance (%)
- Sc - Shading Coefficient

### COMFORT RATING Guide\*

- ◆◆◆◆◆ Highest level of protection/performance
- ◆◆◆◆ High level of protection/performance
- ◆◆◆ Medium level of protection/performance
- ◆◆ Low level of protection/performance
- ◆ No protection

\* COMFORT RATING Guide has been devised by Hunter Douglas Limited with the assistance of Canesis Pty Ltd - an Independent Australian Fibre and Textile Research and Development Company.



Heat Protection



Insulation



Glare Reduction



UV Protection



Shade Factor

## Fire Retardant

Complies with the General Requirements of the Building Code of Australia for Fire Hazard Properties of materials in buildings. Not suitable for use in fire isolated exits of buildings.

Ignitability Index [Range 0-20]	0	Heat Evolved Index [Range 0-10]	0
Spread of Flame Index [Range 0-10]	0	Smoke Developed Index [Range 0-10]	4

# HunterDouglasCommercial

WINDOW COVERINGS

To see how Hunter Douglas Commercial Window Coverings can transform your next project call **1300 733 078**.

[www.hunterdouglascommercial.com.au](http://www.hunterdouglascommercial.com.au)

© Copyright 2008. © Registered Trade Marks of Hunter Douglas Limited (ABN 98 009 675 709).  
10.08\_C7759/Serene