

BLOCKOUT

CAMBRIDGE FABRIC

Applications

Roller Blinds
Roman Shades
Panel Glide

Composition

100% Polyester, twill weave fabric
with flocked backing

Weight

400gsm

Fabric Thickness

0.50mm ± 0.10mm

Roll Width

2.45m

Colour Fastness

6-7 Blue Scale

Stiffness

40mm ± 5mm

Made in Australia

Low VOCs

MULTIVISION® Concept

Product: Cambridge Blockout Fabric Colour: Walnut, Scorpion & Nutmeg



HunterDouglasCommercial

WINDOW COVERINGS

Cambridge Blockout Fabric

features and benefits

100% Polyester

Blockout

All colours in the range are 100% Blockout.

14 Colours

A range of neutrals and great new season designer colours.

Neutral Flocked Backing

Create a colourful interior whilst maintaining a uniform look from the outside of the house. Perfect for areas with strict Strata regulations.

UV Resistant

All colours meet Australian Standards for colour fastness to resist fading.

Versatile

Your customers will be able to match their Roller Blinds and Roman Shades.

Australian Made

Proudly made in Australia to support the local textiles industry.

DURAGUARD® Fabric Protector

DURAGUARD® Fabric Protector effectively repels most stain causing agents with its proven, water based, fluorochemical formula. This fabric protection is totally invisible and has high levels of stain repellence. It makes cleaning and maintaining the fabric much easier

Oeko-Tex “Confidence in Textiles”

Synonymous worldwide with responsible textile manufacture - from the raw materials to the finished product. The Oeko-Tex Standard 100 is a test and certification system for textile raw materials, intermediate and end products at all processing stages that is consistent worldwide. Cambridge Blockout Fabric has been tested for harmful substances according to Oeko-Tex Standard 100.

VOCs

Cambridge Blockout Fabric has been tested and does not exceed the maximum VOC (Volatile Organic Compound) criteria specified by the Green Council of Australia (IEQ-11).

MULTIVISION® Concept

MULTIVISION® is a group of fabrics that are perceived to be the same colour tone, but have different opacities. A number of Cambridge Blockout Fabric colours have been selected for the MULTIVISION® Concept. For more information refer to the Hunter Douglas Commercial MULTIVISION® Brochure.

Solar Optical Properties and COMFORT RATING Guide#

COLOUR	Ts	Rs	As	Tl	Rl	Al	Tuv	Sc	Heat Protection	Insulation	Shade Factor	Glare Reduction	UV Protection
White	0	65	35	0	54	46	0	0.30	◆◆◆◆	n/a	◆◆◆◆	Blockout	◆◆◆◆
Charcoal	0	66	34	0	52	48	0	0.29	◆◆◆◆	n/a	◆◆◆◆	Blockout	◆◆◆◆

Solar Optical Properties Guide

- Ts - Heat Transmittance (%)
- Rs - Heat Reflectance (%)
- As - Heat Absorbance (%)
- Tl - Light Transmittance (%)
- Rl - Light Reflectance (%)
- Al - Light Absorbance (%)
- Tuv - Ultraviolet Transmittance (%)
- Sc - Shading Coefficient

COMFORT RATING Guide#

- ◆◆◆◆ Highest level of protection/performance
- ◆◆◆ High level of protection/performance
- ◆◆ Medium level of protection/performance
- ◆ Low level of protection/performance
- ◆ No protection

COMFORT RATING Guide has been devised by Hunter Douglas Limited with the assistance of Canesis Pty Ltd - an Independent Australian Fibre and Textile Research and Development Company.



Heat Protection



Insulation



Glare Reduction



UV Protection



Shade Factor

Fire Retardancy Information

Complies with the General Requirements of the Building Code of Australia for Fire Hazard Properties of materials in buildings. Not suitable for use in parts of buildings with Special Requirements, i.e. fire isolated exits; public corridors leading to a fire isolated stairway, passageway or ramp; a patient care area of health care buildings; and in a public assembly building (e.g. theatre or hall) not protected with a sprinkler system.

Ignitability Index [Range 0-20]	0	Heat Evolved Index [Range 0-10]	0
Spread of Flame Index [Range 0-10]	0	Smoke Developed Index [Range 0-10]	6

COLOUR RANGE



Note: Colours are as close as printing process allows.