

# SHEER/TRANSLUCENT

## CASABLANCA FABRIC

### Applications

Roller Blinds  
Roman Shades  
Panel Glide

### Composition

100% Polyester

### Weight

Sheer – 160gsm  $\pm$  10gsm  
Translucent – 250gsm  $\pm$  10gsm

### Fabric Thickness

Sheer – 0.44mm  
Translucent – 0.46mm

### Roll Width

2.4m

### Privacy Factor

Sheer – Low-Mid  
Translucent – High

### Colour Fastness

6-7 Blue Scale

### 4 Colours Available

### MULTIVISION® Concept



Product: Casablanca Translucent Fabric Colour: Silver/Grey



**HunterDouglasCommercial**

WINDOW COVERINGS

# Casablanca Sheer/Translucent Fabrics

## features and benefits

### 100% Polyester

### 4 Colours

Modern colour range designed to suit most Australian interiors.

### UV Resistant

All colours meet Australian Standards for colour fastness to resist fading.

### Oeko-Tex "Confidence in Textiles"






Synonymous worldwide with responsible textile manufacture - from the raw materials to the finished product. The Oeko-Tex Standard 100 is a test and

certification system for textile raw materials, intermediate and end products at all processing stages that is consistent worldwide. Casablanca Translucent Fabric has been tested for harmful substances according to Oeko-Tex Standard 100

### MULTIVISION® Concept

MULTIVISION® is a group of fabrics that are perceived to be the same colour tone, but have different opacities. A number of Casablanca Translucent Fabric colours have been selected for the MULTIVISION® Concept. For more information refer to the Hunter Douglas Commercial MULTIVISION® Brochure.

## Solar Optical Properties and COMFORT RATING Guide\*

COLOUR	Ts	Rs	As	Tl	Rl	Al	Tuv	Sc	 Heat Protection	 Insulation	 Shade Factor	 Glare Reduction	 UV Protection
Translucent - Bronze/Brown	0	16	84	0	15	85	0	0.64	◆◆◆◆	◆◆	◆◆◆◆◆◆	Blockout	◆◆◆◆◆◆
Translucent - Gold/Crème	3	49	48	1	46	53	0	0.42	◆◆◆◆◆◆	◆◆	◆◆◆◆◆◆	◆◆◆◆◆◆	◆◆◆◆◆◆
Translucent - Silver/Grey	1	46	53	1	48	51	0	0.44	◆◆◆◆◆◆	◆◆	◆◆◆◆◆◆	◆◆◆◆◆◆	◆◆◆◆◆◆
Translucent - White/Crème	8	73	19	4	66	30	0	0.26	◆◆◆◆◆◆	◆◆	◆◆◆◆◆◆	◆◆◆◆◆◆	◆◆◆◆◆◆
Sheer - Bronze/Brown	17	25	58	18	23	59	10	0.62	◆◆◆◆	◆◆	◆◆◆◆	◆◆◆◆	◆◆◆◆
Sheer - Gold/Crème	30	43	27	29	43	28	17	0.53	◆◆◆◆◆◆	◆◆	◆◆◆◆	◆◆◆◆	◆◆◆◆
Sheer - Silver/Grey	23	36	41	24	38	38	15	0.56	◆◆◆◆	◆◆	◆◆◆◆	◆◆◆◆	◆◆◆◆
Sheer - White/Crème	37	53	10	34	55	11	21	0.48	◆◆◆◆◆◆	◆◆	◆◆◆◆	◆◆◆◆	◆◆◆◆

### Solar Optical Properties Guide

- Ts - Heat Transmittance (%)
- Rs - Heat Reflectance (%)
- As - Heat Absorbance (%)
- Tl - Light Transmittance (%)
- Rl - Light Reflectance (%)
- Al - Light Absorbance (%)
- Tuv - Ultraviolet Transmittance (%)
- Sc - Shading Coefficient

### COMFORT RATING Guide\*

- ◆◆◆◆ Highest level of protection/performance
- ◆◆◆ High level of protection/performance
- ◆◆◆ Medium level of protection/performance
- ◆◆ Low level of protection/performance
- ◆ No protection

\* COMFORT RATING Guide has been devised by Hunter Douglas Limited with the assistance of Canesis Pty Ltd - an Independent Australian Fibre and Textile Research and Development Company.



Heat Protection



Insulation



Glare Reduction



UV Protection



Shade Factor

## Fire Retardant

Complies with the General Requirements of the Building Code of Australia for Fire Hazard Properties of materials in buildings.

Ignitability Index [Range 0-20]	0	Heat Evolved Index [Range 0-10]	0
Spread of Flame Index [Range 0-10]	0	Smoke Developed Index [Range 0-10]	0-1