

# TRANSLUCENT

## PATINASHEER FABRIC

### Applications

Roller Blinds  
Roman Shades  
Panel Glide

### Composition

100% Polyester Trevira CS

### Weight

140gsm (finished weight)

### Fabric Thickness

0.38mm

### Roll Width

2.4m

### Openness Factor

14% average  
(depending on fabric colour)

### Colour Fastness

6-7 Blue Scale

### Stiffness

23mm ± 5mm

### 4 Colours Available

### Low VOCs

### MULTIVISION® Concept



Product: PatinaSheer Translucent Fabric Colour: White

Note: Overseas hardware shown



## HunterDouglasCommercial

WINDOW COVERINGS

# PatinaSheer Translucent Fabric

## features and benefits

### 100% Polyester Trevira CS

### Basket Weave (2/2 Hopsack)

Textured modern design.

### 4 Colours

Modern colour range designed to suit most Australian interiors.

### Excellent Solar Optical Properties

The solar optical properties include heat protection, shade factor, glare reduction and UV protection.

### Light Filtering

The unique weave allows light to filter through and provides a certain level of daytime privacy.

### UV Resistant

All colours meet Australian Standards for colour fastness to resist fading.

### Oeko-Tex "Confidence in Textiles"

Synonymous worldwide with responsible textile manufacture - from the raw materials to the finished product. The Oeko-Tex Standard 100 is a test and

certification system for textile raw materials, intermediate and end products at all processing stages that is consistent worldwide. PatinaSheer Translucent Fabric has been tested for harmful substances according to Oeko-Tex Standard 100.






### VOCs

PatinaSheer Translucent Fabric has been tested and does not exceed the maximum VOC (Volatile Organic Compound) criteria specified by the Green Council of Australia (IEQ-11).

### MULTIVISION® Concept

MULTIVISION® is a group of fabrics that are perceived to be the same colour tone, but have different opacities. A number of PatinaSheer Translucent Fabric colours have been selected for the MULTIVISION® Concept. For more information refer to the Hunter Douglas Commercial MULTIVISION® Brochure.

## Solar Optical Properties and COMFORT RATING Guide\*

COLOUR	Ts	Rs	As	Tl	Rl	Al	Tuv	Sc	 Heat Protection	 Insulation	 Shade Factor	 Glare Reduction	 UV Protection
Natural	48	46	6	41	39	20	21	0.42	◆◆◆◆	◆◆	◆	◆◆	◆
Pepper	38	39	23	28	23	49	19	0.44	◆◆◆◆	◆◆	◆◆	◆◆	◆
Toffee	42	41	17	31	27	42	19	0.44	◆◆◆◆	◆◆	◆	◆◆	◆
White	52	46	2	45	41	14	24	0.44	◆◆◆◆	◆◆	◆	◆◆	◆

### Solar Optical Properties Guide

- Ts - Heat Transmittance (%)
- Rs - Heat Reflectance (%)
- As - Heat Absorbance (%)
- Tl - Light Transmittance (%)
- Rl - Light Reflectance (%)
- Al - Light Absorbance (%)
- Tuv - Ultraviolet Transmittance (%)
- Sc - Shading Coefficient

### COMFORT RATING Guide\*

- ◆◆◆◆ Highest level of protection/performance
- ◆◆◆ High level of protection/performance
- ◆◆ Medium level of protection/performance
- ◆ Low level of protection/performance
- ◆ No protection

\* COMFORT RATING Guide has been devised by Hunter Douglas Limited with the assistance of Canesis Pty Ltd - an Independent Australian Fibre and Textile Research and Development Company.



Heat Protection



Insulation



Glare Reduction



UV Protection



Shade Factor

## Fire Retardant

Complies with the General Requirements of the Building Code of Australia for Fire Hazard Properties of materials in buildings.

Ignitability Index [Range 0-20]	0	Heat Evolved Index [Range 0-10]	0
Spread of Flame Index [Range 0-10]	0	Smoke Developed Index [Range 0-10]	0-1