

TRANSLUCENT

PATINASHEER FABRIC

Applications

Roller Blinds

Roman Shades

Panel Glide

Composition

100% Polyester Trevira CS

Weight

140gsm (finished weight)

Fabric Thickness

0.38mm

Roll Width

2.4m

Openness Factor

14% average
(depending on fabric colour)

Colour Fastness

6-7 Blue Scale


Stiffness

23mm ± 5mm


4 Colours Available

Low VOCs


MULTIVISION® Concept



Pepper



Toffee



Natural



White

Product: PatinaSheer Translucent Fabric Colour: White
Note: Overseas hardware shown



Note: Colours are as accurate as the printing process allows

HunterDouglasCommercial

WINDOW COVERINGS

PatinaSheer Translucent Fabric

features and benefits

100% Polyester Trevira CS

Basket Weave (2/2 Hopsack)

Textured modern design.

4 Colours

Modern colour range designed to suit most Australian interiors.

Excellent Solar Optical Properties

The solar optical properties include heat protection, shade factor, glare reduction and UV protection.

Light Filtering

The unique weave allows light to filter through and provides a certain level of daytime privacy.

UV Resistant

All colours meet Australian Standards for colour fastness to resist fading.

Oeko-Tex "Confidence in Textiles"

Synonymous worldwide with responsible textile manufacture - from the raw materials to the finished product. The Oeko-Tex

Standard 100 is a test and certification system for textile raw materials, intermediate and end products at all processing stages that is consistent worldwide. PatinaSheer Translucent Fabric has been tested for harmful substances according to Oeko-Tex Standard 100.

VOCs

PatinaSheer Translucent Fabric has been tested and does not exceed the maximum VOC (Volatile Organic Compound) criteria specified by the Green Building Council of Australia (IEQ-11).

MULTIVISION® Concept

MULTIVISION® is a group of fabrics that are perceived to be the same colour tone, but have different opacities. A number of PatinaSheer Translucent Fabric colours have been selected for the MULTIVISION® Concept. For more information refer to the Hunter Douglas Commercial MULTIVISION® Brochure.

Solar Optical Properties and COMFORT RATING Guide#

COLOUR	T _s	R _s	A _s	T _L	R _L	A _L	T _{UV}	Sc	Heat Protection	Insulation	Shade Factor	Glare Reduction	UV Protection
Natural	48	46	6	41	39	20	21	0.42	◆◆◆◆	◆◆	◆	◆◆	◆
Pepper	38	39	23	28	23	49	19	0.44	◆◆◆◆	◆◆	◆◆	◆◆	◆
Toffee	42	41	17	31	27	42	19	0.44	◆◆◆◆	◆◆	◆	◆◆	◆
White	52	46	2	45	41	14	24	0.44	◆◆◆◆	◆◆	◆	◆◆	◆

Solar Optical Properties Guide

- T_s - Heat Transmittance (%)
- R_s - Heat Reflectance (%)
- A_s - Heat Absorbance (%)
- T_L - Light Transmittance (%)
- R_L - Light Reflectance (%)
- A_L - Light Absorbance (%)
- T_{UV} - Ultraviolet Transmittance (%)
- Sc - Shading Coefficient

COMFORT RATING Guide#

- uuuuu Highest level of protection/performance
 - uuuu High level of protection/performance
 - uuu Medium level of protection/performance
 - uu Low level of protection/performance
 - u No protection
- # COMFORT RATING Guide has been devised by Hunter Douglas Limited with the assistance of Canesis Pty Ltd - an Independent Australian Fibre and Textile Research and Development Company.



Heat Protection



Insulation



Glare Reduction



UV Protection



Shade Factor

Fire Retardancy Information

Complies with the General Requirements of the Building Code of Australia for Fire Hazard Properties of materials in buildings.

Ignitability Index [Range 0-20]	0	Heat Evolved Index [Range 0-10]	0
Spread of Flame Index [Range 0-10]	0	Smoke Developed Index [Range 0-10]	0-1

HunterDouglasCommercial

WINDOW COVERINGS

To see how Hunter Douglas Commercial Window Coverings can transform your next project call 1300 733 078.

www.hunterdouglascommercial.com.au

© Copyright 2011. Hunter Douglas Limited (ABN 98 009 675 709).
*Registered Trade Marks of Hunter Douglas Limited. 01.11_VV/PATINASHEER