

# BLOCKOUT

## SERENE FABRIC

### Applications

Roller Blinds  
Roman Shades  
Panel Glide

### Composition

100% Polyester

### Weight

350gsm

### Fabric Thickness

0.47mm ± 0.10mm

### Roll Width

2.4m

### Colour Fastness

6-7 Blue Scale

### Stiffness

65mm

### 12 Colours Available

### Low VOCs

### MULTIVISION® Concept



Product: Serene Blockout Fabric Colour: Pepper



## HunterDouglasCommercial

WINDOW COVERINGS

# Serene Blockout Fabric

## features and benefits

### 100% Polyester

### 12 Colours

A range of neutrals & great new season designer colours.

### Neutral Foam Backing

Serene Blockout Fabric allows you to create a colourful interior whilst maintaining a uniform look from the outside of the house. Perfect for units with strict Strata regulations.

### Textured Basecloth

Gives fabric a great look & feel as well as a durable easy clean surface.

### UV Resistant

All colours meet Australian Standards for colour fastness to resist fading.

### Oeko-Tex "Confidence in Textiles"

Synonymous worldwide with responsible textile manufacture - from the raw materials to the finished product. The Oeko-Tex Standard 100 is a test and certification system for textile raw materials, intermediate and end products at all processing stages that is consistent worldwide. Serene Blockout Fabric has been tested for harmful substances according to Oeko-Tex Standard 100.

### VOCs

Serene Blockout Fabric has been tested and does not exceed the maximum VOC (Volatile Organic Compound) criteria specified by the Green Council of Australia (IEQ-11).

### MULTIVISION® Concept

MULTIVISION® is a group of fabrics that are perceived to be the same colour tone, but have different opacities. A number of Serene Blockout Fabric colours have been selected for the MULTIVISION® Concept. For more information refer to the Hunter Douglas Commercial MULTIVISION® Brochure.

## Solar Optical Properties and COMFORT RATING Guide#

COLOUR	Ts	Rs	As	Tl	Rl	Al	Tuv	Sc	Heat Protection	Insulation	Shade Factor	Glare Reduction	UV Protection
White	1	66	33	0	62	38	0	0.29	◆◆◆◆◆	◆◆	◆◆◆◆◆	Blockout	◆◆◆◆◆
Grey	1	63	38	0	61	39	0	0.32	◆◆◆◆◆	◆◆	◆◆◆◆◆	Blockout	◆◆◆◆◆
Black	1	64	35	0	62	38	0	0.31	◆◆◆◆◆	◆◆	◆◆◆◆◆	Blockout	◆◆◆◆◆

### Solar Optical Properties Guide

- Ts - Heat Transmittance (%)
- Rs - Heat Reflectance (%)
- As - Heat Absorbance (%)
- Tl - Light Transmittance (%)
- Rl - Light Reflectance (%)
- Al - Light Absorbance (%)
- Tuv - Ultraviolet Transmittance (%)
- Sc - Shading Coefficient

### COMFORT RATING Guide#

- ◆◆◆◆◆ Highest level of protection/performance
- ◆◆◆◆ High level of protection/performance
- ◆◆◆ Medium level of protection/performance
- ◆◆ Low level of protection/performance
- ◆ No protection

# COMFORT RATING Guide has been devised by Hunter Douglas Limited with the assistance of Canesis Pty Ltd - an Independent Australian Fibre and Textile Research and Development Company.



Heat Protection



Insulation



Glare Reduction



UV Protection



Shade Factor

## Fire Retardant

Complies with the General Requirements of the Building Code of Australia for Fire Hazard Properties of materials in buildings. Not suitable for use in fire isolated exits of buildings.

Ignitability Index [Range 0-20]	0	Heat Evolved Index [Range 0-10]	0
Spread of Flame Index [Range 0-10]	0	Smoke Developed Index [Range 0-10]	5